

INNOLUX DISPLAY CORPORATION

LCD FOG

SPECIFICATION

Customer: _____
Model Name: EE101IA-01D
Date: 2020/08/14
Version: 10

☐ **Preliminary Specification**
☒ **Final Specification**

For Customer's Acceptance

Approved by	Comment

Approved by	Reviewed by	Prepared by

Record of Revision

Version	Revise Date	Page	Content
Pre-Spec.01	2012/11/13	All	Initial Release
Fin-Spec.01	2013/05/20	1	Update Panel power consumption& Weight
		5	Update Vcom from 3.3 to 3.0
		6	Add 3.3 Current Consumption
		7	Update Power sequence
		8	Update LVDS Differential voltage min. values from 200 to 100 mV
		11	Update Panel transmission& Test Conditions 1
		16	Modify Mechanical Drawing
		17~18	Modify Package Drawing
Fin-Spec.02	2014/01/24	2	Modify connect type
		6	Modify unit of I _{GH} and I _{GL} from mA to uA
		7	Modify power sequence
		11	Modify panel transmission typ. values from 3.4% to 5.4%
Fin-Spec.03	2014/08/18	1	Panel size update
Fin-Spec.04	2014/12/29	16	Modify Mechanical Drawing
Fin-Spec.05	2016/11/29	1	Update General Specifications
		6	Update Current Consumption
		6~7	Update Power Sequence
		13	Update Reliability Test Items
Fin-Spec.06	2018/07/12	2-3	Modify Pin Assignment
		4	Modify Operation Specifications
		7-8	Modify Power Sequence
		9	Modify Timing Table
		11	Modify Optical Specifications
		14	Modify Reliability Test Items
		16	Modify Mechanical Drawing
		17-18	Modify Packaging Drawing
Fin-Spec.07	2018/08/13	3	Modify Pin Assignment Description
Fin-Spec.08	2018/11/08	16	Modify Mechanical Drawing
Fin-Spec.09	2019/06/20	16	Modify Mechanical Drawing
Fin-Spec.10	2020/08/14	16	Modify Mechanical Drawing

Contents

1. General Specifications	1
2. Pin Assignment	2
3. Operation Specifications	4
3.1. Absolute Maximum Ratings	4
3.2. Typical Operation Conditions	5
3.3. Power Sequence	7
3.4. LVDS Signal Timing Characteristics	8
3.4.1. AC Electrical Characteristics	8
3.4.2. Timing Table	9
3.4.3. LVDS Data Input Format	10
4. Optical Specifications	11
5. Reliability Test Items	14
6. General Precautions	15
6.1. Safety	15
6.2. Handling	15
6.3. Static Electricity	15
6.4. Storage	15
6.5. Cleaning	15
7. Mechanical Drawing	16
8. Package Drawing	17
8.1. Packaging Material Table	17
8.2. Packaging Quantity	17
8.3. Packaging Drawing	18

1. General Specifications

No.	Item	Specification	Remark
1	LCD size	10.1 inch(Diagonal)	
2	Driver element	a-Si TFT active matrix	
3	Resolution	1280 × 3(RGB) × 800	
4	Display mode	Normally Black, Transmissive	
5	Dot pitch	0.0565(W) × 0.1695(H) mm	
6	Active area	216.96(W) × 135.60(H) mm	
7	Panel size	223.95(W) × 144.24(H) × 1.07(D) mm	Note 1
8	Surface treatment	HC	
9	Color arrangement	RGB-stripe	
10	Interface	LVDS	
11	View direction(Gray Inversion)	free	
12	Panel power consumption	0.7W (Typ)	Note 2
13	Weight	80g(Typ)	
14	inversion	1+2line	
15	IC	HX8288*4&HX8695*1	

Note 1: Refer to Mechanical Drawing.

Note 2: Including T-con Board power consumption

2. Pin Assignment

A 40pin connector is used for the module electronics interface. This model used 196479-40041-3 manufactured by P2 connector

Pin No.	Symbol	I/O	Function	Remark
1	VCOM	P	Common Voltage	
2	VDD	P	Power Supply	
3	VDD	P	Power Supply	
4	NC	---	No connection	
5	NC	---	No connection	
6	NC	---	No connection	
7	GND	P	Ground	
8	Rxin0-	I	-LVDS Differential Data Input	R0-R5, G0
9	Rxin0+	I	+LVDS Differential Data Input	
10	GND	P	Ground	
11	Rxin1-	I	-LVDS Differential Data Input	G1~G5, B0,B1
12	Rxin1+	I	+LVDS Differential Data Input	
13	GND	P	Ground	
14	Rxin2-	I	-LVDS Differential Data Input	B2-B5,HS,VS, DE
15	Rxin2+	I	+LVDS Differential Data Input	
16	GND	P	Ground	
17	RxCLK-	I	-LVDS Differential Clock Input	LVDS CLK
18	RxCLK+	I	+LVDS Differential Clock Input	
19	GND	P	Ground	
20	Rxin3-	I	-LVDS Differential Data Input	R6, R7, G6, G7, B6, B7
21	Rxin3+	I	+LVDS Differential Data Input	
22	GND	P	Ground	
23	NC	---	No connection	
24	NC	---	No connection	
25	GND	P	Ground	
26	NC	---	No connection	

27	NC	---	No connection	
28	NC	---	No connection	
29	AVDD	P	Power for Analog Circuit	
30	GND	P	Ground	
31	LED-	P	LED Cathode	
32	LED-	P	LED Cathode	
33	NC	---	No connection	
34	NC	---	No connection	
35	VGL	P	Gate OFF Voltage	
36	NC	---	No connection	
37	NC	---	No connection	
38	VGH	P	Gate ON Voltage	
39	LED+	P	LED Anode	
40	LED+	P	LED Anode	

I: input, O: output, P: Power

3. Operation Specifications

3.1. Absolute Maximum Ratings

(Note 1)

Item	Symbol	Values		Unit	Remark
		Min.	Max.		
Power voltage	VDD	-0.3	3.9	V	
	AVDD	-0.3	14	V	
	V _{GH}	-0.3	42.0	V	
	V _{GL}	-19	0.3	V	
	V _{GH} -V _{GL}	12	40.0	V	
Operation Temperature	T _{OP}	-20	70	°C	
Storage Temperature	T _{ST}	-30	80	°C	

Note 1: The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

3.2. Typical Operation Conditions


(Note 1)

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Power voltage	VDD	2.3	2.5	2.7	V	Note 2
	AVDD	8.0	8.2	8.4	V	
	V _{GH}	21.7	22	22.3	V	
	V _{GL}	-7.3	-7	-6.7	V	
Input signal voltage	VCOM	2.7	3.0	3.3	V	Note 4
Input logic high voltage	V _{IH}	0.8 VDD	-	3.6	V	Note 3
Input logic low voltage	V _{IL}	0	-	0.2 DV _{DD}	V	

Note 1: Be sure to apply VDD and V_{GL} to the LCD first, and then apply V_{GH}.

Note 2: VDD setting should match the signals output voltage (refer to Note 3) of customer's system board.

Note 4: Typical VCOM is only a reference value, it must be optimized according to each LCM. Be sure to use VR.




3.3. Current Consumption


Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Current for Driver	I_{GH}	300	705	1000	uA	$V_{GH} = 22V$
	I_{GL}	300	705	1000	uA	$V_{GL} = -7V$
	I_{VDD}	50	95	120	mA	$V_{DD} = 2.5V$
	I_{AVDD}	8	45	70	mA	$AV_{DD} = 8.2V$

3.4. Power Sequence

a. Power on:



Symbol	Value			Unit Min.
	Min.	Typ.	Max.	
T1	0.5	2	10	ms
T2	0	5	50	ms
T3	0	5	50	ms
T4	0	6	100	ms
T5	120	130	200	ms


b. Power off:


Symbol	Value			Unit Min.
	Min.	Typ.	Max.	
T6	0.5	2	10	ms
T7	0	7	50	ms
T8	0	5	10	ms
T9	0	1	10	ms
T10	0	2	100	ms

3.5. LVDS Signal Timing Characteristics


3.5.1. AC Electrical Characteristics


Parameter	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
LVDS Differential input high Threshold voltage	R_{xVTH}	-	-	+100	mV	$R_{xVCM}=1.2V$
LVDS Differential input low Threshold voltage	R_{xVTL}	-100	-	-	mV	
LVDS Differential input common mode voltage	R_{xVCM}	0.7	-	1.6	V	
LVDS Differential voltage	$ V_{ID} $	200	-	600	mV	




3.5.2. Timing Table

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Clock Frequency	1/Tc	68.9	71.1	73.4	MHz	Frame rate =60Hz
Horizontal display area	tHD	1280				
HS period time	tH	1410	1440	1470	Tc	
HS Width +Back Porch +Front Porch	tHW+ tHBP +tHFP	60	160	190	Tc	
Vertical display area	tVD	800				
VS period time	tV	815	823	833	tH	
VS Width +Back Porch +Front Porch	tVW+ tVBP +tVFP	15	23	33	tH	





3.5.3. LVDS Data Input Format



4. Optical Specifications

Item	Symbol	Condition	Values			Unit	Remark
			Min.	Typ.	Max.		
Viewing angle (CR≥ 10)	θ_L	$\Phi=180^\circ$ (9 o'clock)	75	85	-	degree	Note 1
	θ_R	$\Phi=0^\circ$ (3 o'clock)	75	85	-		
	θ_T	$\Phi=90^\circ$ (12 o'clock)	75	85	-		
	θ_B	$\Phi=270^\circ$ (6 o'clock)	75	85	-		
Response time	T_{ON}	Normal $\theta=\Phi=0^\circ$	-	10	20	msec	Note 3
	T_{OFF}		-	15	30	msec	Note 3
Contrast ratio	CR		600	800	-	-	Note 4
Color chromaticity	W_X		0.27	0.31	0.35	-	Note 2 Note 5 Note 6
	W_Y		0.28	0.32	0.36	-	
Panel transmission	%		4.8%	5.4%		-	

Test Conditions:

1. VDD=2.5V,, the ambient temperature is 25°C ..
2. The test systems refer to Note 2.
3. The optical specificalitons are measured base on Innolux LCM

Note 1: Definition of viewing angle range




Fig. 4-1 Definition of viewing angle

Note 2: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 30 minutes operation, the optical properties are measured at the center point of the LCD screen. (Viewing angle is measured by ELDIM-EZ contrast/Height :1.2mm, Response time is measured by Photo detector TOPCON BM-7, other items are measured by BM-5A/ Field of view: 1° /Height: 500mm.)




Fig. 4-2 Optical measurement system setup

Note 3: Definition of Response time

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time (T_{ON}) is the time between photo detector output intensity changed from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changed from 10% to 90%.




Fig. 4-3 Definition of response time

Note 4: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of LCD.

Note 6: All input terminals LCD panel must be ground while measuring the center area of the panel.

5. Reliability Test Items

Item	Test Conditions		Remark
High Temperature Storage	Ta = 80℃	120hrs	Note 1, Note 2
Low Temperature Storage	Ta = -30℃	120hrs	Note 1, Note 2
High Temperature Operation	Ts = 70℃	120hrs	Note 1, Note 2
Low Temperature Operation	Ta = -20℃	120hrs	Note 1, Note 2
Operate at High Temperature and Humidity	+40℃, 90%RH	120hrs	Note 1, Note 2
Thermal Shock	-0℃/30 min ~ +50℃/30 min for a total 100 cycles, Start with cold temperature and end with high temperature.		Note 1, Note 2
Package Vibration Test	Random Vibration : ISTA-3A 1Hz~200Hz, Grms=0.53 Half hours for direction of Z.		Note 1
Package Drop Test	Height:60 cm 1 corner, 3 edges, 6 surfaces		Note 1
Electro Static Discharge	± 2KV, Human Body Mode, 100pF/1500Ω		Note 1

Note 1: After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.

Note 2: Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

6.General Precautions

6.1.Safety

Liquid crystal is poisonous. Do not put it in your mouth. If liquid crystal touches your skin or clothes, wash it off immediately by using soap and water.

6.2.Handling

1. The LCD panel is plate glass. Do not subject the panel to mechanical shock or to excessive force on its surface.
2. The polarizer attached to the display is easily damaged. Please handle it carefully to avoid scratch or other damages.
3. To avoid contamination on the display surface, do not touch the module surface with bare hands.
4. Keep a space so that the LCD panels do not touch other components.
5. Put cover board such as acrylic board on the surface of LCD panel to protect panel from damages.
6. Transparent electrodes may be disconnected if you use the LCD panel under environmental conditions where the condensation of dew occurs.
7. Do not leave module in direct sunlight to avoid malfunction of the ICs.

6.3.Static Electricity

1. Be sure to ground module before turning on power or operating module.
2. Do not apply voltage which exceeds the absolute maximum rating value.


6.4.Storage

1. Store the module in a dark room where must keep at $25\pm 10^{\circ}\text{C}$ and 65%RH or less.
2. Do not store the module in surroundings containing organic solvent or corrosive gas.
3. Store the module in an anti-electrostatic container or bag.

6.5.Cleaning

1. Do not wipe the polarizer with dry cloth. It might cause scratch.
2. Only use a soft sloth with IPA to wipe the polarizer, other chemicals might permanent damage to the polarizer.

7.Mechanical Drawing



8.Package Drawing


8.1. Packaging Material Table

No.	Item	Model (Material)	Dimensions(mm)	Unit Weight (kg)	Quantity	Remark
1	Panel Assembly	EE101IA-01D	223.95 x168.34x1.07	0.08	36	
2	EPE spacer	EPE	369 x 221 x 3.2	0.006	36	
3	Dust-Proof Bag	PE	700 x 530	0.058	1	
4	Tray	PET	472 x 310 x 16	0.196	19	
5	Cushion	EPE	518x 356 x 90	0.140	2	
6	Drier	SILICA GEL	100 x 75	0.032	2	
7	Carton	Corrugated Paper	530 x 367 x 260	0.95	1	
8	Total weight	8.17 Kg \pm 5%				

8.2. Packaging Quantity

(1) FOG quantity per PET-Tray:	2pcs
(2) Total FOG quantity in Carton:	18 layer x 2pcs/PET-Tray = 36pcs

8.3. Packaging Drawing



- (1) Box Dimensions : 530(L)*367(W)*260(H)
- (2) 36 Panel/Carton